



Fiberglass Mesh 5621

DESCRIPTION:

Our Fiberglass Mesh 5621 is a woven fiberglass composite fabric, intended for use with Plexibond Coating over cracked or worn athletic courts.

PACKAGING:

The Fiberglass mesh comes in rolls of 35 inches (89cm) wide by 150 ft (45.7m) long.

TECHNICAL CHARACTERISTICS:

| Property | Imperial | Metric | Testing |
|--------------------|------------------------|-----------------------|-------------|
| Construction: Warp | 20 yarns/inch | 79 yarns/10 cm | ASTM D-3775 |
| Construction: Weft | 10 yarns/inch | 39 yarns/10 cm | ASTM D-3775 |
| Weight: | 1.9 oz/yd ² | 65.0 g/m ² | ASTM D-3776 |
| Thickness: | 0.006 per inch | 0.150 per mm | ASTM D-1777 |
| Weave: | Plain | Plain | |
| Min. Tensile: Warp | 85 lb/in | 370 N/2.54 cm | ASTM D-5035 |
| Min. Tensile: Weft | 80 lb/in | 350 N/2.54 cm | ASTM D-5035 |

All statements herein are expressions of opinion, which we believe to be accurate and reliable, but are presented without guarantee or responsibility on our part. Statements concerning possible use of our product are not intended as recommendations for their use in the infringement of any patent. No patent warranty of any kind, expressed or implied, is made or intended. Values presented above are nominal and only to be used as guidelines.

SURFACE USES:

- Plexibond System: For surfacing existing coated and uncoated asphalt tennis courts having minor crazing and surface cracks.

For further details on installing Plexibond with Fiberglass mesh over cracked or worn courts, please refer to the Plexibond-Fiberglass Installation Guide.